


Kolana bez szwu  
wg ANSI B 16.9



Wykonywane w gatunkach:  
1.4306, 1.4404

DN	Wymiar	Schedule	a mm	Waga kg
	D x s			
1/2" 15	21,34x2,11	Sch 10S	38,10	0,07
	21,34x2,77	40S	38,10	0,08
	21,34x3,73	80S	38,10	0,10
3/4" 20	26,67x2,11	Sch 10S	28,50	0,07
	26,67x2,87	40S	28,50	0,08
	26,67x3,91	80S	28,50	0,10
1" 25	33,40x2,77	Sch 10S	38,10	0,12
	33,40x3,38	40S	38,10	0,15
	33,40x4,55	80S	38,10	0,19
1 1/4" 32	42,16x2,77	Sch 10S	47,60	0,20
	42,16x3,56	40S	47,60	0,26
	42,16x4,85	80S	47,60	0,34
1 1/2" 40	48,26x2,77	Sch 10S	57,20	0,27
	48,26x3,68	40S	57,20	0,36
	48,26x5,08	80S	57,20	0,49
2" 50	60,30x2,77	Sch 10S	76,20	0,46
	60,30x3,91	40S	76,20	0,65
	60,30x5,54	80S	76,20	0,89
2 1/2" 65	73,03x3,05	Sch 10S	95,30	0,78
	73,03x5,16	40S	95,30	1,30
	73,03x7,01	80S	95,30	1,70
3" 80	88,90x3,05	Sch 10S	114,30	1,15
	88,90x5,49	40S	114,30	2,05
	88,90x7,62	80S	114,30	2,75
3 1/2"	101,60x3,05	Sch 10S	133,40	1,60
	101,60x5,74	40S	133,40	2,85
4" 100	114,30x3,05	Sch 10S	152,40	2,00
	114,30x6,02	40S	152,40	3,90
	114,30x8,56	80S	152,40	5,35
5"	141,30x3,40	Sch 10S	190,50	3,50
	141,30x6,55	40S	190,50	6,60
6" 150	168,30x3,40	Sch 10S	228,60	4,95
	168,30x7,11	40S	228,60	10,20
	168,30x10,92	80S	228,60	15,40
8" 200	219,10x3,76	Sch 10S	304,80	9,70
	219,10x8,18	40S	304,80	21,00
	219,10x12,70	80S	304,80	31,00