

**Redukcje spawane
wg DIN 11851
symetryczne**

Wykonywane w gatunkach: 1.4301(7), 1.4404

Wymiar	a	b	c	d
DN	mm	mm	mm	mm
15 / 10	16	10	11,2	1,5
20 / 10	20	10	18,7	1,5
20 / 15	20	16	7,5	1,5
25 / 10	26	10	30,0	1,5
25 / 15	26	16	18,7	1,5
25 / 20	26	20	11,2	1,5
32 / 15	32	16	30,0	1,5
32 / 20	32	20	22,5	1,5
32 / 25	32	26	11,2	1,5
40 / 15	38	16	41,0	1,5
40 / 20	38	20	33,5	1,5
40 / 25	38	26	22,5	1,5
40 / 32	38	32	11,2	1,5
50 / 20	50	20	55,5	1,5
50 / 25	50	26	44,8	1,5
50 / 32	50	32	33,5	1,5
50 / 40	50	38	22,5	1,5
65 / 25	66	26	74,5	2,0
65 / 32	66	32	63,5	2,0
65 / 40	66	38	52,5	2,0
65 / 50	66	50	30,0	2,0
80 / 32	81	32	91,5	2,0
80 / 40	81	38	80,2	2,0
80 / 50	81	50	58,0	2,0
80 / 65	81	66	28,0	2,0
100 / 50	100	50	93,0	2,0
100 / 65	100	66	63,5	2,0
100 / 80	100	81	35,5	2,0
125 / 50	125	50	140,0	2,0
125 / 65	125	66	110,0	2,0
125 / 80	125	81	82,0	2,0
125 / 100	125	100	46,7	2,0
150 / 50	150	50	186,3	2,0
150 / 65	150	66	156,8	2,0
150 / 80	150	81	128,7	2,0
150 / 100	150	100	93,3	2,0
150 / 125	150	125	46,7	2,0
200 / 125	200	125	139,5	2,0
200 / 150	200	150	93,0	2,0

**Redukcje spawane
wg DIN 11851
niesymetryczne**

Wykonywane w gatunkach: 1.4301(7), 1.4404

Wymiar	a	b	c	d
DN	mm	mm	mm	mm
25 / 10	26	10	44,0	1,5
25 / 15	26	16	27,5	1,5
32 / 20	32	20	33,0	1,5
32 / 25	32	26	16,5	1,5
40 / 20	38	20	49,5	1,5
40 / 25	38	26	33,0	1,5
40 / 32	38	32	16,5	1,5
50 / 25	50	26	66,0	1,5
50 / 32	50	32	49,5	1,5
50 / 40	50	38	33,0	1,5
65 / 32	66	32	93,5	2,0
65 / 40	66	38	77,0	2,0
65 / 50	66	50	44,0	2,0
80 / 40	81	38	118,2	2,0
80 / 50	81	50	85,2	2,0
80 / 65	81	66	41,2	2,0
100 / 50	100	50	137,4	2,0
100 / 65	100	66	93,4	2,0
100 / 80	100	81	52,2	2,0
125 / 80	125	81	120,5	2,0
125 / 100	125	100	68,5	2,0
150 / 100	150	100	137,5	2,0
150 / 125	150	125	68,5	2,0

