

Rury bez szwu wg ISO - DIN 17 458									
Tolerancja: ISO 1127/2462									
Wykonywane w gatunkach: 1.4301, 1.4306, 1.4541, 1.4571									
DN	Wymiar D x s	Waga kg/mb	DN	Wymiar D x s	Waga kg/mb	DN	Wymiar D x s	Waga kg/mb	
10	17,20x1,60	0,625	40	48,30x3,20	3,614	100	114,30x2,60	7,272	
	17,20x2,00	0,761		48,30x3,60	4,029		114,30x3,05	8,496	
	17,20x2,30	0,858		48,30x4,05	4,487		114,30x3,20	8,902	
	17,20x2,90	1,038	50	60,30x1,60	2,352		114,30x3,60	9,979	
	17,20x3,20	1,122		60,30x2,00	2,920		114,30x4,00	11,048	
15	21,30x1,60	0,789		60,30x2,60	3,757		114,30x4,50	12,372	
	21,30x2,00	0,967		60,30x2,90	4,168		114,30x5,40	14,725	
	21,30x2,60	1,217		60,30x3,20	4,575		114,30x6,02	16,322	
	21,30x2,90	1,336		60,30x3,60	6,288		114,30x6,30	17,037	
	21,30x3,20	1,450		60,30x4,50	5,639		114,30x8,56	22,665	
20	26,90x1,60	1,014	60,30x6,30	8,519	125	139,70x4,00	13,864		
	26,90x2,00	1,247	65	76,10x2,00		3,711	139,70x5,00	16,864	
	26,90x2,60	1,582		76,10x2,60		4,785	139,70x6,30	21,044	
	26,90x3,20	1,889		76,10x2,90		5,315	139,70x7,10	23,570	
	25	33,70x1,60		1,286		76,10x3,20	5,841	150	168,30x3,40
33,70x2,00		1,588		76,10x3,60	6,535	168,30x4,50	18,457		
33,70x2,60		2,025		76,10x4,05	8,068	168,30x5,00	20,400		
33,70x2,90		2,237		76,10x4,50	8,605	168,30x6,30	25,556		
33,70x3,20		2,444		76,10x6,30	8,900	168,30x7,11	28,690		
33,70x3,60	2,713	80		88,90x2,00	3,711	168,30x10,97	43,210		
33,70x4,05	3,007			88,90x2,60	4,785	219,10x6,30	33,570		
32	42,40x1,60		1,635	88,90x2,90	5,315	200	219,10x8,18		43,200
	42,40x2,00		2,023	88,90x3,05	5,841		219,10x12,70		65,637
	42,40x2,60		2,591	88,90x3,20	6,535		250		273,00x8,80
	42,40x3,20		3,141	88,90x3,60	7,689			273,00x9,27	61,220
	42,40x3,60		3,498	88,90x4,05	8,605			300	323,90x9,93
42,40x4,05	3,889		88,90x5,49	10,500	323,90x12,70	98,948			
40	48,30x1,60		1,871	88,90x6,30	13,030				
	48,30x2,00		2,319	88,90x7,62	15,509				
	48,30x2,60	2,975							

Rury bez szwu wg DIN - DIN 17 458									
Tolerancja: ISO 1127/2462									
Wykonywane w gatunkach: 1.4301, 1.4306, 1.4541, 1.4571									
DN	Wymiar D x s	Waga kg/mb	DN	Wymiar D x s	Waga kg/mb	DN	Wymiar D x s	Waga kg/mb	
10	14,00x1,50	0,326	65	76,10x2,00	3,711	100	108,00x2,50	6,604	
	14,00x2,00	0,470		76,10x2,60	4,785		108,00x3,20	8,397	
15	20,00x1,50	0,695		76,10x2,90	5,315		108,00x3,60	9,411	
	20,00x2,00	0,901		76,10x3,20	5,841		108,00x4,00	10,417	
	20,00x2,50	1,096		76,10x3,60	6,535		108,00x5,00	12,896	
20	25,00x2,00	1,152		76,10x4,05	8,605		108,00x6,30	16,043	
	25,00x2,50	1,409		76,10x4,50	8,068		125	133,00x4,00	12,921
	25,00x3,00	1,605		76,10x6,30	11,011			133,00x5,00	16,026
	25,00x4,00	2,103		88,90x2,00	3,711			133,00x6,30	19,987
	25,00x5,00	2,504		88,90x2,60	4,785			159,00x4,50	14,039
25	30,00x2,00	1,402	88,90x2,90	5,315	150	159,00x5,00		18,457	
	30,00x2,60	1,784	88,90x3,05	5,841		159,00x6,30	20,455		
	30,00x3,00	2,028	88,90x3,20	6,535					
	30,00x4,00	2,604	88,90x3,60	7,689					
	30,00x4,00	2,604	88,90x4,05	8,605					
32	38,00x2,00	1,803	88,90x5,49	11,466	200	199,00x2,50	10,417		
	38,00x2,60	2,305	88,90x6,30	13,030		199,00x3,00	12,921		
	38,00x3,00	2,629	88,90x7,62	15,509		199,00x4,00	17,425		
	38,00x4,00	3,405	108,00x2,50	6,604		199,00x5,00	21,929		
	38,00x5,00	4,132	108,00x3,20	8,397		199,00x6,30	26,433		
40	44,50x2,00	2,128	108,00x3,60	9,411		250	249,00x2,50	12,921	
	44,50x2,60	2,728	108,00x4,00	10,417			249,00x3,00	15,425	
	44,50x3,00	3,021	108,00x5,00	12,896			249,00x4,00	20,929	
	44,50x4,00	4,056	133,00x4,00	12,921			249,00x5,00	25,433	
	44,50x5,00	5,371	133,00x5,00	16,026			249,00x6,30	30,937	
50	57,00x2,00	2,754	133,00x6,30	19,987	300	299,00x2,50	15,425		
	57,00x2,60	3,542	159,00x4,50	14,039		299,00x3,00	17,929		
	57,00x2,90	3,929	159,00x5,00	18,457		299,00x4,00	22,433		
	57,00x4,00	5,308				299,00x5,00	26,937		
	57,00x5,00	6,510				299,00x6,30	31,441		

Rury bez szwu wg ANSI B 16.9			
Wykonywane w gatunkach: 1.4306, 1.4404			
DN	Wymiar d x s	Schedule	Waga kg/mb
1/2"	21,34x2,11	Sch 10S	1,016
	21,34x2,77	40S	1,288
	21,34x3,73	80S	1,645
3/4"	26,67x2,11	Sch 10S	1,298
	26,67x2,87	40S	1,710
	26,67x3,91	80S	2,228
1"	33,40x2,77	Sch 10S	2,125
	33,40x3,38	40S	2,541
	33,40x4,55	80S	3,287
1 1/4"	42,16x2,77	Sch 10S	2,732
	42,16x3,56	40S	3,441
	42,16x4,55	80S	4,531
1 1/2"	48,26x2,77	Sch 10S	3,155
	48,26x3,68	40S	4,108
	48,26x5,08	80S	5,493
2"	60,30x2,77	Sch 10S	3,990
	60,30x3,91	40S	5,521
	60,30x5,54	80S	7,596
2 1/2"	73,03x5,16	Sch 40S	8,769
	88,90x3,05	Sch 10S	6,557
	88,90x5,49	40S	11,466
3"	88,90x7,62	80S	15,509
	101,60x5,74	Sch 40S	13,778
	114,30x3,05	Sch 10S	8,496
4"	114,30x6,02	40S	16,332
	114,30x8,56	80S	22,665
	141,30x6,55	Sch 40S	22,101